

XV500

Debris Box Container



- **12 Gauge Steel Construction**
Built to last
- **Angle Frame Reinforced**
3/16" x 1-1/2" Angle Frames
- **78"W x 72"W x 8' Long**
other sizes available
- **Versatile Mounting**
mounts on any dump or flat bed



The Xtreme choice of professional landscapers and municipalities

Construction	One-piece construction. Manufactured with 12-gauge steel panels and 3/16" x 1-1/2" thick angle frame supports.
Door	Top hinged door, completely framed with 4 vertical 3/16" x 2" x 2" angle frames supports and 4 horizontal 3/16" x 2" x 2" angle frame supports. The panels are 12-gauge steel. The door has a hose support and a flexible rubber gasket with 16" diameter hole to accommodate the exhaust hose.
Hinges	4 cleave-type hinges which are constructed of 3/8" thick steel with a 3/4" thick pin.
Door Latch	A unique easy-open latch eliminates door rod binding. The convenient handle easily locks and unlocks the box door for dumping.
Rubber Gasket	The 12, 14 or 16" diameter hole is positioned to support the bottom of the exhaust hose 40" from the bottom of the box. Other heights and hole diameters are available as an option. Please specify diameter when ordering.
Lifting Eyes	4 lifting eyes, two on each corner are welded to the top of the box allowing the box to be lifted easily with a crane or hoist.
Handles	4 convenient handles are welded to the long sides of the box, two at 3 feet from the bottom and two at six feet from the bottom.
Inside of Box	Smooth interior for easy dumping and equipped with heavy-duty rubber deflector to stop debris from hitting the front of the box.
Floor Panel	Box floor is a short floor panel that allows the box to over hang the back of the truck by as much as 12 inches.
Box Top and Screen	The top is two-thirds vented with 1/2" expanded flattened steel. The screen is supported with 3/16" x 1-1/2" angle frames.
Dimensions	78"* wide x 72" tall x 8' long (with additional length increments of 6 inches) *Please note the angle frame and handles add 4-3/4" to the width. The absolute <u>minimum</u> truck bed width needed for a 78" wide box is 81".
Paint	The box is primed with a rust inhibitor primer and painted with two coats of automotive quality paint.



Easy to open and close latch mechanism makes closing the door simple and virtually effortless.



Heavy duty cleave-type hinges with 3/4" pin.



The top screen is made of 1/2" expanded steel.



Sold and Serviced By:

XTREME
VAC

www.xtremevac.com