



Self-Contained Debris Collector

DCL800SM

Kubota WG3800-G-E3
4-cylinder Gasoline
engine rated at 87HP.

- 28” suction impeller
- 16” dia. x 144” long urethane suction hose
- 3-Axis hose boom with in-cab controls

The DCL800SM has the best suction of any unit in it’s class.
Contact ODB to order yours today!

DCL800SM



*Specifications subject to change at any time without notice.

*Standard color is white.

*Units shown with options.



Follow us at ODBCompany

800-446-9823



DCL800SM

Automated Debris Collection Loader-Chassis Mounted



Specifications

Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 4-groove power band.

Hoist

Gear driven hydraulic pump powers underbody hoist that dumps to 52 degrees.

Hopper

Container constructed of 12 gauge steel with vented top and top hinged rear door. Available in 14, 20, 25 & 30 cu.yd. capacities.

Truck Body

Freightliner M2-106 chassis with dual steering.

Fuel Tank

40-gallon polyethylene fuel tank.

Options

- Eco Mode
- Fluid drive coupler in lieu of standard clutch
- Bottom Exhaust for hopper
- Air scoop to direct exhausted air to the rear
- Perforated top screens with 3/16" holes
- Urethane coated liners for blower housing
- Rotary self-cleaning air screen for radiator
- Urethane suction hose in lieu of rubber
- Driver's side (street) pick up
- Chipper door with trailer hitch package
- Two (2) surface mounted LED flashers
- LED Traffic directional light bar on rear

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Throttle

Remote electric throttle and clutch engagement.

Hose Boom

3-Axis hose boom powered by electric/hydraulic pump with proportional in-cab controls.

Hose

16" x 144" urethane intake hose with steel nozzle.

Impeller

28" diameter suction impeller with six 3/8" thick T-1 steel blades. Replaceable 1/4" thick abrasion resistant steel liners.

Camera

Rear backup camera with 5.6" color screen.

Lights

LED type DOT trailer lights. Two amber LED flashers in the rear.

Paint

All components are pre-painted with PPG paint. Hopper - standard white, other custom paint colors available as options.

800-446-9823

www.odbc.com

5118 Glen Alden Dr. Richmond, VA 23231